

IN THE CLAIMS:

1. (Previously presented) A refrigerator drawer assembly comprising:

a pan support comprising a wire member having a first side and a second side;

a first bracket coupled to said first side using a first coupling system;

a second bracket coupled to said second side using a second coupling system different than the first coupling system wherein said second bracket is substantially identical to said first bracket; and

wherein said first coupling system comprises a U-shaped wire member, and said second coupling system comprises at least two hooks, said first bracket coupled to said U-shaped wire member, said second bracket coupled to said hooks.

2. (Original) A refrigerator drawer assembly in accordance with Claim 1 wherein said first and second brackets are coupled to said wire member such that they are removable without using tools.

3. (Original) A refrigerator drawer assembly in accordance with Claim 1 wherein each said bracket comprises a first rail with slots and a second rail with holes, said first rail of one bracket coupled to one of said first and second sides and said second rail of the other bracket is coupled to the other of said first and second sides.

4. (Original) A refrigerator drawer assembly in accordance with Claim 3 wherein said first rail of said first bracket is coupled to said first side, and said second rail of said second bracket is coupled to said second side.

5. (Original) A refrigerator drawer assembly in accordance with Claim 4, wherein said first coupling system comprises a U-shaped wire member, and said second coupling system comprises at least two hooks.

6. (Canceled)

7. (Original) A refrigerator drawer assembly in accordance with Claim 1, wherein said first coupling system comprises a U-shaped wire member aligned with a right front portion of said pan support, and said second coupling system comprises a U-shaped

wire member extending exterior to a plane defined by a left front portion of said pan support, said first bracket coupled to said U-shaped wire member aligned with said right front portion, said second bracket coupled to said U-shaped wire member extending exterior to the plane defined by said left front portion.

8. (Canceled)

9. (Canceled)

10. (Canceled)

11. (Currently amended) A method for assembling a refrigerator drawer assembly, said method comprising:

forming a pan support wire member from a continuous wire, the pan support wire member having a first side and a second side;

providing a plurality of substantially identical brackets including a first bracket and a second bracket;

~~removably coupling the first bracket to the first side in a first manner~~
removably coupling the first bracket to the first side using a first U-shaped member; and

~~removably coupling the second bracket to the second side in a second manner different from the first manner~~
removably coupling the second bracket to the second side using a plurality of hooks.

12. (Canceled)

13. (Canceled)

14. (Canceled)

15. (Canceled)

16. (Canceled)

17. (Currently amended) A bracket-pan support assembly comprising:

a pan support wire member comprising a first side including a U-shaped member and a second side including a plurality of hooks; and

a bracket comprising:

a sidewall;

a first rail extending from said sidewall, said first rail comprising a plurality of slots sized to receive ~~a first said first~~ a first U-shaped member ~~extending from a pan support wire member~~; and

a second rail extending from said sidewall, said second rail comprising at least one of: ~~— a one of a plurality of slots sized to receive a second U-shaped member extending from the —~~ pan said pan support wire member; and

~~— and a plurality of apertures each sized to receive a hook extending from the —~~ pan said pan support wire member; and

wherein said first and said second rails each comprise an inwardly turned lip portion.

18. (Canceled)

19. (Previously presented) A bracket in accordance with Claim 17 wherein said second rail comprises a plurality of slots sized to receive a second U-shaped member extending from the pan support wire member.

20. (Previously presented) A bracket in accordance with Claim 17 wherein said second rail comprises a plurality of apertures each sized to receive a hook extending from the pan support wire member.

21. (Currently amended) A refrigerator drawer assembly comprising:

a pan support comprising a continuously formed wire member having a first side and a second side, said first side defining a channel and said second side including a plurality of hooks;

a first bracket coupled to said first side such that said first bracket is removable without tools, said first bracket forming a lip positioned within said channel; and

a second bracket coupled to said second side such that said second bracket is removable without tools, said second bracket defining a plurality of apertures for receiving a corresponding hook of said plurality of hooks.

22. (Previously presented) An assembly in accordance with Claim 21 wherein said second bracket substantially identical to said first bracket.

23. (Previously presented) An assembly in accordance with Claim 21 wherein said first bracket coupled to said first side with a first coupling system, said second bracket coupled to said second side with a second coupling system different from said first coupling system.